

PLAKA – CORRUGATED END

Corrugated end and stop for plastic distance tube

REF 04.01.02 - Version V01 - 12/08/2020



Manufacturer's specifications :

Description



This product is used at the end of round plastic distance tubes.




The corrugated end allows a good bond with the concrete and reduces water infiltration.

These ends have not to be removed after the concrete pour. These ends are closed afterwards with special corrugated stops.

Application fields

Corrugated ends are used where the watertightness of concrete constructions at the place of formwork distance tubes have to be improved.

Dimensions

Schema	Dimensions			
	Reference code	Φ_i/Φ_e mm	p/Box	Kg/100
 Corrugated ends 	RS5650	20/24	500	0.64
	RS5657	22/26	500	0.85
	RS5658	22/28	500	1.28
	RS5661	26/30	500	1.06
	RS5655	32/38	500	1.28
 Corrugated stops	RS5652	20	500	0.30
	RS5654	22	500	0.34
	RS5662	26	500	0.37
	RS5656	32	500	0.64

©Copyright protected

This sheet, written with great care, supersedes all previous versions. The technical information on the design, models, illustrations, design values and specifications are believed to be accurate. We make no warranties (expressed or implied) as to its accuracy and assumes no liability in connection with non suitable use of this product. We reserve the right to modify the contents of this form without prior notice.