

PLAKA - COLMASTIC

Hydrophilic leveling putty based on bentonite
REF 05.05.03 - Version V01 - 14/08/2020



Description



Colmastic is a green hydrophilic levelling putty to be used in conjunction with Colmarub.

Application of Colmarub to the rough substrate will ensure 100% contact of the Colmarub in the joint.

Hydrophilic, swells in contact with water.

100% compatible with Colmarub.

Good sticking power to both the concrete surface and the Colmarub.


Application field

Colmastic is used to level rough surfaces in support of the application of Colmarub.

Properties

Mechanical properties	
Appearance	Green putty.
Consumption	The necessary quantities depend on the length of the various (construction) joints which need to be levelled out before receiving Colmarub.
Swelling capacity in contact with water	Swells more than 200% of the original dry volume.
Storage	Colmastic should be stored under cover, clear of the ground. Protect the materials from all sources of moisture and frost.
Health and safety	Consult the relevant Material Safety Data Sheet.

Dimensions

Material dimensions				
Design	Description	Reference	Weight	Packaging
	Colmastic	DNC	5 kg/pail	60 pails/ pallet

©Copyright protected

This sheet, written with great care, supersedes all previous versions. The technical information on the design, models, illustrations, design values and specifications are believed to be accurate. Plaka make no warranties (expressed or implied) as to its accuracy and assumes no liability in connection with non suitable use of this product. We reserve the right to modify the contents of this form without prior notice.